

SERIES	AC200
AVAILABLE OPTIONS	Electric Heated
MODELS	39E5
AVAILABLE VOLTAGES	208V/240V/1, 208V/240V/3, 480V/3, 600V/3

OVERVIEW




Series 200 – Lower velocity units rated for installation up to a maximum 8' (2.5m). Designed primarily for single doors or smaller vestibules. Ideal for drive through windows where a higher velocity may be required when mounting the unit farther from the window.

Control panel included with every air curtain. Complete with - 3 speed control, Thermostat and 2 heat settings.



Electric Heated



Air Flow

GENERAL CHARACTERISTICS		
MODEL		39E5
Heat Output	kBTU/h	18.4
	kW	5.4
Air Volume	cfm	883
	m ³ /h	1500
Max. Door Height	ft	8.2
	m	2.5
Temperature rise	°F	18.9
	°C	10.5
Length	ft	3.3
	mm	1000
Dimensions (L x W x H)	in	41 x 9 x 9
	mm	1040 x 225 x 225
Weight	lb	33.1
	kg	15
Motor Input	hp	0.14
	W	100
Sound Level at 5 m (distance)	dB(A)	52
*Max. Current unit (208V)	A	16.1
Maximum motor current	A	0.5
*Max. Current heating elements	A	
480 V		6.9
600 V		5.6

* See page 6.